


# Polar<sup>®</sup> Focus



Ultimate Line Array Rigging

**PY0-ZBH-550**

**PY0 Quick Disconnect Fitting  
with Zbeam<sup>®</sup> Half**

PY0 Quick Disconnect Fitting with Zbeam Half allows an easy connection to Polar Focus<sup>®</sup> line array accessories.

This product allows for two point support of a cluster for permanent installations, with a center service pick point, with full pan control. Not for use with two hoists.

\* If you need to lift your cluster with two chain hoists, you must use the PY0-ZBR, for Zbeam with Rocker Arm.

Polar Focus Ultimate Line Array Rigging. For more assistance, call our audio rigging consultants at (413) 586-4444.




***Figure 1. Polar Focus PY0 Universal Joint Fitting with Zbeam<sup>®</sup> Half***

*Allows for two point support of a cluster for permanent installations with a center service pick point with full pan control.*

See [www.linearrayframes.com](http://www.linearrayframes.com) for pan control, roof attachment, OEM products, line array frames and manufacturer-specific rigging.

# Polar<sup>®</sup> Focus



## Ultimate Line Array Rigging

### Architectural Specification:

The rigging device shall allow for pan control while under load. The pan control shall retain a set pan angle through the use of a rated friction bearing. Upper rigging points shall consist of two 3/4" pad-eyes and one centrally located 1/2" eye-nut. The rigging device shall be manufactured of welded structural steel and grade 5 hardware. It shall have a Working Load Limit of 550 lbs (250 kg) with a 10:1 design factor. The rigging device shall be the PY0-ZBH-550.

Overall Length:	15" (381mm)
Overall Height:	8.7" (221mm)
Overall Width:	5.5" (140mm)
Max. Usable length:	13" (330mm)
Weight:	9.9 lbs ( 4.5 kg)
Primary Material:	Structural Steel
Finish:	Powder Coat Black
Working Load Limit:	550 lbs (250 kg)

